

# **BODY**

# Overpaintable Body

#### **DESCRIPTION**

BODY is a peely monocomponent overpaintable plastic protective with high sound proof power. Protects from humidity, salt and crushed asphalt abrasion.

#### **CHARACTERISTICS**

- -Easy application;
- -It doesn't contain lead, tar, asbestos or chlorinated hydrocarbons.

## **TECHNICAL SPECIFICATIONS**

Product type Alkyd resin.

Colour Black/grey/white.

Aspect Peely.

Packaging 1 kg - 2 kg. Specific weight 1970 g/l.

Optimal thickness 50-60 Micron.

V.O.C. 400 g/l.

## **USEFUL TIPS**



Adviced pressure

(with pressurised spray gun)4 - 5 ATM.Distance from support20 - 30 cm.

Number of hands 1 - 2.

Interval between hands 15 minutes. Adviced thickness 300 micron.



AIR DRYING

Dust free 20 - 30 minutes. Overpainting 3 - 4 hours.



#### SANITARY AND SAFETY REGULATIONS

For professional use.

The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.