

PSA

WORLD REFINISH PAINTS

SMALTO NITRO

Aluminum wheels

DESCRIPTION

SMALTO NITRO aluminum wheels is a nitrosunthetic monocomponent enamel of easy application even without polishing, optimal yield and easy polishing.

SMALTO NITRO aluminum wheels possesses extremely fast air drying and several hands may be applied.

CHARACTERISTICS

- Easy application;
- It doesn't contain lead, tar, asbestos or chlorinated hydrocarbons.

TECHNICAL SPECIFICATIONS

Product type	Nitrosyntetic resin.
Colour	Alluminum grey.
Packaging	1 lt.
Specific weight	990 g/l.
V.O.C.	715 g/l.

USEFUL TIPS



Pressure	4 - 5 ATM.
Distances from support	20 - 30 cm.
Number of hands	1 - 2.
Interval between hands	5 - 10 minutes.
Adviced thickness	100 - 150 micron.



AIR DRYING



Duest free	5 - 7 minutes.
Total	10 - 15 minutes.



SANITARY AND SAFETY REGULATIONS

For professional use.

www.psa-car.it

The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.

MAXICAR - PSA GROUP

VIA L. DA VINCI, 21/23 - TEL. 0935 684005 - 85426 - FAX 0935 686228 - 94015 PIAZZA ARMERINA (EN)

MAIL info@psa-car.it P.IVA 01087700868