

PSA

WORLD REFINISH PAINTS

SMALTO NITRO

Matte black

DESCRIPTION

SMALTO NITRO matte black is a nitrosynthetic monocomponent enamel of easy application even without polishing, optimal yield and easy polishing.

SMALTO NITRO matte black possesses extremely fast air drying and several hands may be applied.

CHARACTERISTICS

- Easy application;
- It doesn't contain lead, tar, asbestos or chlorinated hydrocarbons.

TECHNICAL SPECIFICATIONS

Product type	Nitrosynthetic resin.
Colour	Matte black.
Packaging	1 lt.
Specific weight	990 g/l.
V.O.C.	570 g/l.

USEFUL TIPS



Pressure	4 - 5 ATM.
Distance from support	20 - 30 cm.
Number of hands	1 - 2.
Interval between hands	5 - 10 minutes.
Advised thickness	100 - 150 micron.



AIR DRYING



Dust free	5 - 7 minutes.
Total	10 - 15 minutes.



SANITARY AND SAFETY REGULATIONS

For professional use.

www.psa-car.it

The information and data contained in this data sheet are based on measurements and the experience acquired in good faith, they are given to the customer who is entitled to verify the application and the definition of eligibility to the use it intends to make. MAXICAR PSA GROUP LTD assumes no responsibility for the results obtained in the specific application made by the user.

MAXICAR - PSA GROUP

VIA L. DA VINCI, 21/23 - TEL. 0935 684005 - 85426 - FAX 0935 686228 - 94015 PIAZZA ARMERINA (EN)

MAIL info@psa-car.it P.IVA 01087700868